



## MODEL 282EP-60 & 282GP-60 EDSON PERISTALTIC PUMP OUT CARTS

*60 Gallon Waste Collection Cart  
For Holding Tank Pump Outs  
Electric & Gas Powered*

### PERFORMANCE FEATURES

- No Clog, No Spill, No Smell
- Easy Fill & Off Load Operation
- Pump Out Rates to 20 GPM
- Self Priming Suction from Heights Up to 25 ft. (7.6m)
- Easily Moved Around with Trailer Dolly or Electric Cart
- Low Maintenance

### DESIGN FEATURES

- Aluminum Peristaltic Pump
- Welded Aluminum Cart with Pneumatic Tires
- Quick Clamp Plumbing & Hose Assemblies
- Electric or Gas Powered
- Commercial Roto Molded Tank
- Ball Hitch for use with Electric Carts
- Hose Rack

### GENERAL DESCRIPTION

Edson's Peristaltic Pump Out Cart is a convenient, easy to use, totally self-contained waste collection system. It is ideal for marinas that cannot connect a pump out direct to a shore side sewer system but need to collect and transport the waste within the marina. The pump out cart uses the Edson unique plumbing and hose assemblies that allows for the tank to be safely emptied by the pump while virtually eliminating the chance of accidental spillage. The pump and hose assemblies are available as separate items for those who want to use them with their own tanks and carts, trailers or boats.



**Pictured:  
Electric Powered 282EP- 60  
Complete With Tow Dolly**

#### Pump Performance:

- Volume - Max Rating For The Pump is 35 GPM  
Cart Set-up With 1hp Electric 20 GPM
- Suction Lift - to 29 ft./8.8 m
- Discharge Head - to 65 ft./19.8 m

#### Pump Construction:

- Pump Body-Aluminum Alloy w/ Steel Rotor and Shaft
- Power - 1HP, Single Phase, 110V, TEFC w 20 AMP ON/OFF Switch or 5 HP Gas Engine
- Cast Aluminum Mounting Frame with Baked On Polyurethane Coating
- Welded Aluminum Cart w/Pneumatic Tires & Ball Hitch (Tow Dolly Included)
- 60 Gal. Polyethylene Waste Tank

#### Hose Assembly:

- 1 1/2" Premier Hose
- Sight Glass/Check Valve
- 25' Length Standard
- Complete Set of Deck Adapters

### ORDERING INFORMATION

| DESCRIPTION<br><i>See Price List For Other Models</i> | WEIGHT<br>(Lbs/Kgs) | ORDER NO. |
|---|---------------------|-----------|
| Peristaltic Electric Pump Out Cart                    | 300/134.4           | 282EP-60  |
| Peristaltic Gas Pump Out Cart                         | 300/134.4           | 282GP-60  |



## PERISTALTIC PUMP OUT CART



### COMPONENTS

The 282EP-60 is powered by a 1 hp electric motor that allows the pump to be operated on a 20 amp 120V electrical circuit.

The 282GP-60 is powered by a 5 hp gas engine.



Transfer Hose - 20' x 1 1/2" ID PVC hose assembly used to extend discharge line when needed to empty collection tank.



Pump Out Hose Assembly - Comes complete with 90° ball valve, sight glass, cam lock adapter and complete set of deck fill adapters. 25ft. assembly is standard. Longer or shorter assemblies are optional.



Tow Dolly - Built with pneumatic tires and 1 7/8" ball, it can support up to 700 lb. tongue weight.

### DIMENSIONS

