# EDS#N PUMPS Data Sheet

# 28210 Pumpout Skid - 100 Gallon

Fits Pickup Truck Beds measuring 38.5" (inside width) or Wider.

# **Design Features**

- 304 Stainless Steel
- Tubing Construction
- Stainless Steel Hose Rack
- 100 Gallon PE Tank
- 20' Discharge Hose

## General Description

The 28210 (100gal) Pumpout Skid is is an ideal way to provide pump out service throughout the marina without installing plumbing. Great for multiple applications and transitioning between various vehicles: Boats, Carts, Trucks, or wherever you can fit it!

Boat yards frequently need to pump out a boat either when in dry dock or when pulling the boat for the season. The portable design can be integrated into a plumbing infrastructure to provide a fixed station though out the marina and become portable as needed.

The versatile skid is designed to accept our diaphragm pump options, or the powerful peristaltic options shown below.



Weight

Skid, Tank (empty), 20' Discharge Hose, Hose Rack

210 lbs | 95.25 kg

Pump with Gasoline Motor

# **Pump Options for Skid**



#### #25261 DOUBLE DIAPHRAGM

- 3/4HP 120V 1PH
- 25' Suction Lift
- 25' Discharge Head
- Up to 25 GPM
- Poly Construction



#### #120EL SINGLE DIAPHRAGM

- 3/4HP 120V 1PH
- 12' Suction Lift
- 12' Discharge Head
- Up to 38 GPM
- Aluminum or Bronze




#### #28631 SILVER PERISTALTIC

- Up to 2HP | 1PH OR 3PH
- 24' Suction Lift
- Up to 100' Discharge Head
- Up to 22 GPM
- Marine Grade Aluminum

HONDA GASOLINE ENGINES ALSO AVAILABLE.





EDSON Corporation
146 Duchaine Boulevard
New Bedford, MA 02745-1292
(508) 995-9711 Fax: (508) 995-5021

**28210 Frame** 

1/10th Size
Date
October 1 st, 2015

Drawn By

RWB

A-3291-1



25 ft. Order No. 261-25-150 33 ft. Order No. 261-33-150 50 ft. Order No. 261-50-150 Custom Length Assemblies 5ft to 100ft

The Edson Pumpout Hose (length 25 Ft [picture to the left], 1½" ID x 2" OD, EPDM tube with Polyethylene helix) comes complete with all fittings and adapters including 90° ball valve and sight glass. It's two part construction of smooth inner bore and rugged outer spiral cap provides a pump out hose that is corrosion resistant, extremely flexible, crushproof, collapse-proof and abrasive resistant. It can be used with any suction pump and at 104 degrees F has a vacuum rating of 28" Hg and pressure rating of 35 psi.

# #261-25-150

25ft Assembly Shown Deck Adapters (Included)



### Assembly Components (Included)



## Assembly Instructions:

Insert appropriate size deck fitting adapter to fit boat waste/sewage connector. NOTE: Use threaded adapters when possible for best results. Potty wand is for portable toilets only. **NOT FOR BILGES** 

